

HDBW1235E-W

1080P H.265 Dome Wi-Fi Camera

HDBW1235E-W delivers 2MP live monitoring with a choice of 2.8mm or 3.6mm lens options, it supports the latest H.265 compression which can save up to 50% bandwidth and storage. With IP67 & IK10 certified, the camera can be used outdoors under different weather conditions and can perfectly resist vandalism.



1080P FHD Video
See more than 720P



H.265 Codec
The latest and most efficient codec type



24/7 Protection
Excellent night vision,
feel safe even in complete darkness



IP67&IK10
Weather and vandal proof



Human Detection
Get instant alert when moving
human target is detected



Easy4ip Cloud
Cloud management for your
easy monitoring

Stay close with what you care



With Easy4ip Cloud, you'll have access to what you care as long as Internet is available. You can record daily or motion videos on Easy4ip Cloud and playback anytime anywhere.

Specifications

Camera

1/2.9" 2Megapixel progressive CMOS
2MP(1920 x 1080)
Night Vision: 30m distance
2.8mm or 3.6mm lens option
Field of View : 2.8mm:106°(H), 56°(V), 128°(D)
3.6mm:83°(H), 44°(V), 98°(D)

Video

Video Compression : H.265/H.264
Up to 25/30fps Frame Rate
16x Digital Zoom

Notice Management

Motion Detection
Human Detection
Configurable region and schedule

Network

1 x 100Mbps Ethernet port
Wi-Fi: IEEE802.11b/g/n, 50m open field
ONVIF Profile S&G, CGI
Easy4ip app: iOS, Android

Auxiliary Interface

Micro SD Slot (up to 128GB)
WPS/Reset button

General

DC 12V1A Power supply
Power Consumption: <6.5W
Working Environment:-10°C~+50°C, Less than 95%RH
IP67, IK10
Dimensions: Φ 110mm \times 81mm (Φ 4.3inch \times 3.2inch)
Weight: 435g (0.96lb)
CE, FCC, UL

What's in the box

- 1x Camera
- 1x Power Adapter
- 1x Ethernet Cable
- 1x Quick Start Guide
- 1x Screw Package
- 1x Screw Driver
- 1x Waterproof Connector
- 1x Installation Position Map

Accessory



PFA136
Junction box



PFB203W
Wall mount



PFA152
Pole mount